CE

HETA

Declaration of Performance EN

Regulation No. 305/2011
DoP-Kube 10-2799-2026

1. Model identifier	Kube 10
2. Intended use or uses of the construction product, in accordance with the applicable technical specification	Room heater solid fuel, space heating in residential building
3. Name and contact address of the manufacturer	Heta A/S, Jupitervej 22, DK-7620 Lemvig. heta@heta.dk
4. System of assessment and verification of constancy of performance of the construction product	System 3
5. Notified body relevant to the assessment and verification of constancy of performance	Danish Technological Institute, DK-8000 Aarhus Notified body No. 1235. Report nr. 300-ELAB-2799-EN

6. Essential characteristics

Mechanical resistance and stability	120 kg Load bearing capacity
Fire safety	
Minimum distance to combustible materials	Minimum distances in mm
Bottom (dB) Ceiling (dC) Rear (dR) Side (dS) Furniture in front (dP) Corner (45°) (dS!) Floor front (dF) Side radiation area (dL) Ceiling/ Mantel (dC!) Door to hearth (dB!)	0 (<65K) 750 275/ (120 Insulated) 400/ (350 Insulated) 1000 125 (70 Insulated) 500 (If dB! is 290 dF will be 0(<65K)) 0 (<65K) 530 290 (Lower than 290, dF must be 500 in front and comply with EU Std. for fire safety: A2-s1,d0)
Hygiene, health and the environment	
Emissions at nominal heat output (Harmonized technical specification EN 16510-2-1-2022)	
CO (≤) 1500 mg/m³ Nox (≤) 200 mg/m³ OGC (≤) 120 mg/m³ Particles (≤) 40 mg/m³	515 mg/Nm³ 89 mg/Nm³ 32 mgC/Nm³ at 13% O_2 18 mg/Nm³

Safety and accessibility in use

Data for installation to a chimney at nominal heat output	
Flue gas outlet temperature	260 °C
Minimum flue draught	12 Pa
Flue gas mass flow	3,3 g/s
Data for installation to a chimney regarding fire safety test heat output	
Fire safety of installation to the chimney	T400G

Energy economy and heat retention

Appliance's thermal output and energy efficiency at nominal heat output		
Space heat output		4,0 kW
Efficiency	≥ 75%	η 84%
Seasonal space heating efficiency at appliance's nominal heat output	≥ 65%	η_s 74%
Energy efficiency		112
		A+

7.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf the manufacturer of **30.04.2026**

HETA
Jupitervej 22, DK-7620 Lemvig
TLF: +45 96 63 06 00
Martin Bach

In case of any change of the above-mentioned product, this Declaration of Performance becomes invalid.
Heta A/S, Jupitervej 22, DK-7620 Lemvig, Tlf. +45 9663 0600, www.hetaheating.com