DECLARATION OF PERFORMANCE (DOP)

	NO. 90583600-CPR-20140306	
1.	Product Type:	Freestanding stove Scan 83
2.	Type, batch or serial number:	Scan 83 series (Scan 83-1, Scan 83-2, Scan 83-3, Scan 83-4, Scan 83-5, Scan 83-6, Scan 83-7, Scan 83-8)
3.	Intended use of the product:	Heat distribution/room heating Without hot water supply Fuel type: Wood
4.	Name and Address of the manufacturer:	Scan A/S Glassvænget 3-9 5492 Vissenbjerg
5.	Contact address:	No relevance
6.	AVCP System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V	System 3
7.	Notified body: Test report no:	RWE NB-No 1427 FSPS-Wa 2249 EN
8.	Declared performance	
	Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
	·	
	Essential characteristics	Performance
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out	Performance A1 Minimum distances in mm: Rear: 100 Sides: 400 Front: 900 NPD
	Fire safety Reaction to fire Distance to combustible materials	A1 Minimum distances in mm: Rear: 100 Sides: 400 Front: 900
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out	A1 Minimum distances in mm: Rear: 100 Sides: 400 Front: 900 NPD CO [0,07 %] NOx [106 mg/Nm³] OGC [55 mg/Nm³]
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out Emission of combustion products	A1 Minimum distances in mm: Rear: 100 Sides: 400 Front: 900 NPD CO [0,07 %] NOx [106 mg/Nm³] OGC [55 mg/Nm³] Dust [23 mg/Nm³]
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out Emission of combustion products Surface temperature	A1 Minimum distances in mm: Rear: 100 Sides: 400 Front: 900 NPD CO [0,07 %] NOx [106 mg/Nm³] OGC [55 mg/Nm³] Dust [23 mg/Nm³] Pass
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out Emission of combustion products Surface temperature Electrical safety	A1 Minimum distances in mm: Rear: 100 Sides: 400 Front: 900 NPD CO [0,07 %] NOx [106 mg/Nm³] OGC [55 mg/Nm³] Dust [23 mg/Nm³] Pass -
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out Emission of combustion products Surface temperature Electrical safety Cleanability	A1 Minimum distances in mm: Rear: 100 Sides: 400 Front: 900 NPD CO [0,07 %] NOx [106 mg/Nm³] OGC [55 mg/Nm³] Dust [23 mg/Nm³] Pass - Pass
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out Emission of combustion products Surface temperature Electrical safety Cleanability Maximum water operating pressure	A1 Minimum distances in mm: Rear: 100 Sides: 400 Front: 900 NPD CO [0,07 %] NOx [106 mg/Nm³] OGC [55 mg/Nm³] Dust [23 mg/Nm³] Pass - Pass -
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out Emission of combustion products Surface temperature Electrical safety Cleanability Maximum water operating pressure Flue gas temperature at nominal heat output [EN]	A1 Minimum distances in mm: Rear: 100 Sides: 400 Front: 900 NPD CO [0,07 %] NOx [106 mg/Nm³] OGC [55 mg/Nm³] Dust [23 mg/Nm³] Pass - Pass - T [280°C]

DECLARATION

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Morten Bach (R&D LAB)

Vissenbjerg, March 6, 2014





(Signatute